



STRONGARM M50

PRODUCT	STRONGARM M50
CRASH CERTIFIED	ASTM F2656-07 M50, P2
DUTY CYCLE	Continuous duty*
HORSEPOWER	2 hp
OPEN/CLOSE	6 to 8 seconds depending on arm
LENGTH	
EMERGENCY FAST CLOSE TIME	5 to 7 seconds depending on arm length
CLEAR OPENING	12 ft to 24 ft in 2 ft increments (366 cm to 732 cm in 61 cm increments) Call for custom arm length
INGRESS PROTECTION	IP56
TEMP. RATING	-40° F to 158° F (-40° C to 70° C) using environmentally friendly uniflow fluid -10° f to 158° f (-23° c to 70° c) using
BIODEGRADABLE FLUID	
1 PHASE POWER	208/230 VAC, 50/60 Hz 20A
3 PHASE POWER	208/230 VAC, 50/60 Hz 20A 380/480 VAC, 50/60 HZ 15A
FOUNDATION	6 x 6 x 2 ft (183 x 183 x 61 cm) 4,000 psi concrete, #6 rebar, grade 60
COMMUNICATION	RS-232, RS-485
WARRANTY	5 year

Check out our other HVM products at supamaxx.com.au

1300 225 521 | supamaxx.com.au

© SUPAMAXX 2019